

# Criteria for Review of Visible Dormers

Adopted by the Commission on Chicago Landmarks Permit Review Committee  
May 6, 2010.

The following additional criteria shall be considered in evaluating whether proposed new dormers on front-facing gable-roofed cottages in the Old Town Triangle District will have an adverse effect on the district when such dormers would be visible from the public right-of-way. Such factors as relative visibility of any proposed dormer, given the building size, the site conditions (e.g., unusually wide side yards or a double lot) and the surrounding context, as well as the proposed location, size, massing and design of the dormer itself, will be considered in the review of such projects on a case-by-case basis.

Note that depending on the specific conditions and circumstances, there may still be limited or no potential to construct a visible dormer even with these additional criteria. Also, due to the high degree of visibility, these criteria do not apply to visible dormers on the street side of a front-gabled cottage on a corner property, and such dormers would therefore not be allowed under these criteria; Additionally, these criteria would generally not apply to new or expanded visible dormers on buildings which already have visible dormers, particularly where such dormers are highly visible and do not conform with these additional criteria. Finally, visible dormers that are not necessary in order to achieve minimum code-required interior ceiling heights will not be considered pursuant to these additional criteria.

1. Alternative dormer locations and/or configurations are not possible such as where the dormer or other addition would otherwise not be visible from the public way;
2. The proposed visible dormer is minimized in size and configuration to minimize its visibility from the public way and its impact on the historic rooflines of the building as much as possible (e.g., inseting the rear portion of a dormer so that it is effectively screened from public view by the front portion of the dormer and thereby reduces its visibility);
3. Regardless of visibility, no more than one dormer (including existing dormers) is proposed per building side; furthermore, if a dormer exists and/or is proposed for both sides of the building, the visibility of each individual dormer as well as the cumulative visibility (e.g., if both dormers would be visible from the same vantage points) is taken into consideration in evaluating the potential adverse effect;
4. The proposed visible dormer is set back from the front facade of the building as much as possible, but with a setback of at least 25 feet or 60% of the length of the principal (main) gable roof of the building, whichever is greater;
5. The roof of the proposed dormer is as low as possible relative to the existing main ridge height of the building, generally at least 1'-0" lower than the main ridge, and in no instance higher than the main ridge [note that, depending on the specific conditions, there may still be limited or no potential to achieve minimum code-required interior ceiling heights];
6. The proposed dormer has a simple gable or shed roof, depending on the dormer's location, size and visibility, with as perceptible a slope as possible, and generally minimal overhangs;
7. The proposed dormer is sided with materials compatible with that of the building and, depending on the dormer's relative visibility, generally also the color of the roofing material to further minimize visibility;
8. The proposed dormer does not have windows facing the front of the property; and,
9. The design and detailing of the proposed dormer is simplified.

## **Criteria for Visible Dormers on 1-1/2 story Masonry Cottages in the Ukrainian Village and Extension Districts**

Given historic precedent, and in recognition of the exceptionally small size of these cottages and that the overwhelming preponderance of them already have dormers, staff has developed guidelines in order to encourage appropriately-designed, visible new dormers compatible with the district's historic character. Staff recommends that dormers be approved on 1½-story masonry cottages in the Ukrainian Village District and the Ukrainian Village District Extension provided that:

1. Dormers are set back from the front façade of the building by at least 1/3 the length of the building, but ideally further back;
2. Dormers are designed with a ridge height no taller than 1'-0" lower than the main ridge height of the building;
3. Dormers are hip- or gable-roof style, with an appreciable slope;
4. The dormers are sided with compatible materials, such as brick or wood siding;
5. Dormers are no more than 6'-0" in length; and
6. Ideally one dormer, but no more than two separate dormers (including existing dormers), may be constructed per building side, depending on: the length of the building and the size, location, visibility, and other design characters of any existing dormers.

*Adopted by the Permit Review Committee on January 5, 2005.*



City of Chicago  
Richard M. Daley, Mayor

Commission on  
Chicago Landmarks

Peter C. B. Bynoe  
Chairman

Room 516  
320 North Clark Street  
Chicago, Illinois 60610-4711  
(312) 744-3200 (Voice)  
(312) 744-2958 (TDD)  
(312) 744-9140 (FAX)

Draft, presented 9/7/94 to Permit Review Committee

## Design Guidelines for Dormers in the Villa District

- New policy, to allow new, visible dormers
- only in the Villa District
- like original dormers, should always be secondary features

### Proposed Guidelines :

size: less than or equal to 1/3 (or 1/2) of the length of the original house.

location: ideally, centered on the length of the house, but in no case should they be closer to the facade than 1/4 to 1/3 of the length of the building.

type: shed-roof style so as to minimize height and impact

roof: Must have appreciable slope, (approx 15 degrees) so as not to appear like a room addition. Pitch should start approx. 1' or more below ridgeline of original house.

windows: Whenever possible, windows on dormer should line up with windows below.

materials and details: Compatible with existing, in case of brick house : stucco or wood siding; in a frame house : wood siding. Asphalt or wood shingles for roof. Details simple, light trim, again, to minimize the effect on the original house.

number: One, or in rare cases, two separate dormers per side.

