## **6.0 IMPLEMENTATION**

### **Project Information**

ect Location		
Project Address		
Type of Project (land use)		
Size of Project		
Is this a river dependent or critical service use?	□ Yes	□ No
Character Zone	□ Northwest Zone □ North Branch Zone □ Loop Zone	□ South Branch Zone' □ Southwest Zone □ Bubbly Creek Zone
30 ft. river setback (as verified by plat of survey)	□ Yes	□ No
Public Access	□ Yes	□ No
ago River Design Guidelines Multi-Use Path		
Multi-Use Path  3.2.1 Design Criteria	□ Yes	□ No
Multi-Use Path	□ Yes □ Yes □ N/A, please describe	□ No □ No
Multi-Use Path  3.2.1 Design Criteria	□ Yes	

72 Chicago River Design Guidelines Chapter 6

3.3	Furnishings		
	3.3.1 Site Furnishing Guidelines		
	Materials, select all the apply	<ul><li>□ Stainless Steel</li><li>□ Galvanized Steel</li><li>□ Powder Coated Steel</li></ul>	<ul> <li>□ Hardwoods, describe below</li> <li>□ Recycled Plastic Lumber, describe below</li> <li>□ Other, please describe below</li> </ul>
	Benches & Tables, on per 250 linear feet (LF) of river frontage.	LF of river frontage Total Benches Total Tables	
	Trash and Recycling Receptacles, one metal trash and one metal recycling receptacles per 250 linear feet (LF) of river frontage	LF of river frontage Total Trash Receptacles Total Recycling Receptacles	
	Railings	□ Yes	□No
	Comments, please note which section from the list above you're describing		
3.4	Seating and Gathering Areas		
	3.4.1 Seating Area Guidelines		
	Location, one per 500 linear feet (LF) of river frontage.	LF of river frontage Total Seating Areas	
	Furnishings, Each seating area should provide a minimum of two benches and one trash receptacle.	Total Benches Total Trash Receptacles	
3.5	Lighting		
		an example of an acceptable product data sheet.	
	Fixture Height, recommended between 14-30 feet tall	□ Yes, between 14-30'	□ Other, please describe below
	Color Temperature, LED bulbs that provide white light with a color temperature of 3000K or below.	□ 3000K or below	□ Other, please describe below
	Light Pollution	□ Dark Sky Compliant	□ N/A
	Additional Features	□ Yes, please describe below	□No
	Security Lighting	□ Yes	□ No
	Comments, please note which section from the list above you're describing		

3.6	Wayfinding and Signage		
	3.5.1 Lighting Guidelines6.1 Signage Guidelines		
	Brand and Identity	□ Yes □ N/A	□ No
	Directional Signage, indicate total signs	□ Yes □ N/A	□ No
	Mile Marker, locate every quarter mile	□ Yes □ N/A	□ No
	Regulatory Signage, indicate total signs	□ Yes □ N/A	□ No
	Identity Signage, indicate total signs	□ Yes □ N/A	□ №
	Comments, please note which section from the list above you're describing		
3.7	Landscaping		
	3.7.1 Preservation and Restoration Guidelines		
	Preservation, preserve existing habitat and plantings	□ Yes □ N/A	□ No
	Disturbance, minimize site disturbance	□ Yes □ N/A	□ No
	Protection, protect existing vegetation during construction by installing tree protection fence	□ Yes □ N/A	□ No
	Tree Preservation and Removal, preserve mature, healthy, native shade and evergreen trees	□ Yes □ N/A	□ No
	3.7.2 Plant Selection Guidelines		
	Plant Selection, per Appendix 7.4. Identify total number of plants selected from Appendix list.	Submergent Emergent Riparian Upland	
	Fencing, 4-6' ornamental metal fence for vehicular use areas, 4' ornamental metal fence for non-vehicular use areas	□ Yes , height	□ No
	Trees, 2 per 25 LF of river frontage for vehicular use areas, 1 per 25 LF for non-vehicular use areas	LF of river frontage Total Vehicular Area Trees Total Non-Vehicular Area Trees	
	Hedges, continuous hedge on the river side of fence is required for vehicular use areas	□ Yes □ N/A	□ №
	Foundation Plantings, required for non-vehicular use areas	□ Yes □ N/A	□ No
	Comments, please note which section from the list above you're describing		

Chicago River Design Guidelines Chapter 6

74

3.8 Riverbank Treatments			
3.8.1 Riverbank Guidelines			
Existing sloped riverbank is retained and improved	to be □ Yes	□ No	
3.9 River Edge Treatments			
3.9.1 River Edge Guidelines			
Describe the proposed river stabilization and enhanceme treatments.	-		
3.10 Sloped Bank Treatments			
3.10.1 Sloped Bank Guidelines			
O.T.O.T. Cloped Ballit Galdoniloo			
Describe the proposed slope treatments.	ed bank		
3.11 Vertical Bulkhead or Seawall Trea	ıtments		
3.11.1 Vertical Bulkhead or Seawal	l Guidelines		
Describe the proposed vertice bulkhead and seawall guidelest treatments.			
3.12 Guidelines for Improvements Out			
	ssing of New Structures and Buildings		
Placement, locate buildings vehicular areas outside of the setback		□ No	
River-facing façade, river-fac should be designed as a prir major façade	_	□ No	
Massing and Articulation, low lower buildings with active from adjacent to river setback are back massing along river. Low buildings behind low buildings	ontage □ N/A a. Step cate taller	□ No	
Neighborhood Transitions, s height of buildings to transitions scale of adjacent neighborhood	on to the $\square$ N/A	□ No	
First Floor, activate first floor buildings with direct access multi-use path		□ No	
Wildlife, incorporate bird-frie design standards into buildin		□ No	
Sunlight, river corridor shoul sunlight for approximately six per day		□No	

	3.12.2 Screening Guidelines		
	Outdoor Storage, if necessary, storage areas should be locatede beyond the minimum 30' setback area	□ Yes , height ————————————————————————————————————	□ No
	Materials, select all that apply	<ul><li>□ Poured-in-Place Concrete</li><li>□ Split Face Concrete Masonry Units</li><li>□ Ground Face Concrete Masonry Units</li></ul>	□ Heavy Wood □ Other, please describe below
	Walls and Fences, screening walls and fences should be planted with vines at the base	□ Yes □ N/A	□ No
	Access, fencing that separates the riverfront from the outside of the setback area should be avoided	□ Yes □ N/A	□ No
3.13 Trai	nsition Between Adjacent Developments		
	Describe the proposed transitions and treatments between adjacent developments		

76 Chicago River Design Guidelines Chapter 6

#### Menu of Improvements

4.1 Overview			
4.1.1 Application			
PD Projec	t Size	□ Large, >1,980 LF of riverfront □ Medium, 660-1,980 LF of riverfront	□ Others
		Total Expected Menu Items Required # of Priority Menu Items	
4.3 Nature			
4.3.2 New Natur	alized Shoreline (priority)		
	he proposed new naturalized		
shoreline	mprovements		
4.3.3 Stormwate	r Management Best Practices	(priority)	
<u> </u>			
Describe t	he proposed stormwater		
managem	ent best practices		
4.2.4 Aquatia Wi	Idlife Habitats (priority)		
4.5.4 Aquatic Wi	idille Habitats (priority)		
Describe t	he proposed aquatic wildlife		
habitats			
<b>*</b>			
4.3.5 Robust Upl	and Habitats		
Deceribe t	as proposed rebust		
upland hal	ne proposed robust pitats		
4.3.6 Increased	Setback		
Describe t setback	he proposed increased		
Selback			
127:Lorgo Div	erfront Park		
4.5.7 Large Kive			
4.3.7 .Large Rive			
Describe t	he proposed large riverfront		
	he proposed large riverfront		

4.4 Recreation	
4.4.2 Access to Water and Docking Facilities	
Describe the proposed access to water	
and docking facilities	
4 4 3 Expanded Seating Areas	
4.4.3 Expanded Seating Areas	
Describe the proposed expanded	
seating areas	
4.4.4 Riverfront Overlooks	
Describe the proposed riverfront	
overlooks	
4.4.5 Recreational Areas	
Describe the proposed recreational	
areas	
4.4.6 Support Amenities	
Describe the proposed support	
amenities	
amonido	

Chicago River Design Guidelines Chapter 6

78

I.5 Connectivity	
4.5.2 Underbridge Connections	
Describe the proposed underbridge connections	
4.5.3 Enhanced Connections to Street & Trans	sportation Network
Describe the proposed enhanced	
connecttions to the street and transportation network	
4.5.4 Elevator / Increased Accessibility	
Describe the proposed elevator / increased accessibility	
4.5.5 Cantilevered & Floating Walkways	
Describe the proposed cantilevered and floating walkways	
4.5.6 Interpretive Signage	
Describe the proposed interpretive signage	
4.5.7 Public Art & Specialty Lighting	
Describe the proposed public art and	
specialty lighting	

# .hess

#### LINEA 450 LVC

The LINEA series features distinctly linear design qualities and exceptional versatility. Perceptively capturing today's minimal design philosophy, the reduced form is sure to retain its validity far into the future. It is available in three mounting heights in single or twin mounting configurations. The pedestrian-scale model is 15 feet, with intermediate and larger sizes at 20 and 26 feet, respectively, giving proper scale for a variety of applications. Units for bi-level mounting are available, where the street-side luminaire is mounted high and a second fixture is mounted on the sidewalk side at a lower height for pedestrian illumination. An LED illuminating bollard for low-level pathway illumination complements the family of products. CSA Listed for Wet Locations

Specification

For example only, use of this cut sheet does not imply approval of or preference for product shown. This sheet is for demonstration purposes only.



	LED	Color					Pole		
Model	Module	Temperature	Distribution	Volt	Mounting	Pole	Mat	Finish	Option
LN450	2LVC - 2 modules	WW -3000K	T2 - Type II	UNV - 120-277V	A - Single Mount	15SR - 15' Straight Rectangular	A - Aluminum	SG - Silver Grey	DIM - 0-10vDC Dimming
		NW - 4000K	T <sub>3</sub> - Type III		B - Twin Mount	X - Other (specify)	S - Steel	DG - Dark Grey	N - None
			T4 - Type IV					GG - Graphite Grey	
								BLK - Matte Black	
								BRZ - Dark Bronze	
								CC - Custom Color	

**Ordering Information** 

Specifications are subject to change without notification

HessAmerica > Products > Lighting Products > Pole Mounted Luminaire > LINEA https://www.hessamerica.com/Products/Lighting/Pole\_Mounted\_Luminaire/LINEA/

Page 1